## 250 kW Electric Container Boiler

www.crosshireservices.ie



## Heating & Cooling

The highly specialist 250kW Electric Container Boiler delivers 250kW of LTHW output from an electrical supply, with absolutely no need for any fuel input.



Overview	
Output	264 kW
Temperature Range	20 - 90°C
Power Supply	415v 3ph
Running Current	375 Amps
Plug Type	Hard Wired
Maximum Working Pressure	4.5 Bar
Boiler Type	ACV E-TECH 22kW
Number of Boilers	12
Control	Individual Stat per Boiler
Header	Steel Vertical Mounted
Design Flow	11.35 m³/hr
Pump Capacity	24.1 m <sup>3</sup> /hr
Pump Type	Lowara FCE 40-160/15
Pump Control	Hydrovar Inverter
System Expansion	320 ltrs
Electrical Distribution	400A Interlocked Panel
Safety - Mechanical	4.5 Bar PRV
Safety - Electrical	External Emergency Stop
Flexible Hose Connections	2"Storz
Recirculation Connection	2"Storz
Noise Level	55 dBA @ 1 mtr
Handling Options	Fork Pockets, 4 Point Lifting
Weight	1800 kg
Dimensions (WxDxH)	1,310 x 2,030 x 1,780mm



We are happy to provide further information



1890 247 266

DUBLIN +353 01 4048770 CORK +353 021 4930870 NI +44 078 92728580



info@crosshireservices.ie



www.crosshireservices.ie