

TROTEC TEH 100 Electric Heater

www.crosshireservices.ie



Heating & Cooling



Mobile heating solution for construction sites, industry and agriculture or for heating unventilated rooms with condensation-free warmth.

Concealed underneath the TEH 100's steel sheet construction with protective coating is an especially developed chassis, which was elaborately flow-optimized for maximum system efficiency so that focussed hot air can be streamed via hose distances of up to 15 m without turbulence losses.

Model	TEH 100 Electric Heater		
Heating capacity	Stage Max. [kW]	18 Stage Max. [kcal]	15,400
Amount of air	Stage Max. [m ³ /h]	1,785	
Air pressure	Stage Max. [Pa]	130	
Temperature increase	in [°C]	38	
Fans	Axial		
Electrical values	Mains connection	400 V/50 Hz	
Nominal current consumption [A]	27.2		
Power input [kW]	18		
Electric connection	Connection plug	CEE 32 A, 5-pin	
Sound values	Distance 1 m [dB(A)]	69	
Hose connector	Diameter [mm]	300 mm	
Dimensions (L x W x H)	400 mm x 400 mm x 480 mm		
Weight	29.5 [kg]		



We are happy to provide further information



1890 247 266

DUBLIN +353 01 4048770
CORK +353 021 4930870
NI +44 078 92728580



info@crosshireservices.ie



www.crosshireservices.ie