

TTR 200 Desiccant Dehumidifier

0.35 Kg/Hr Removal Capacity

www.crosshireservices.ie



Heating & Cooling



- Continuously regulatable
- Quick and easy filter replacement
- Extremely easy maintenance and service-friendly construction
- Suitable for installation in false ceilings
- Housing made of sheet steel, galvanized and powder coated
- Can be stacked to save space
- Leightweight and easy-to-handle
- Quality premium components
- Practice optimized German industrial design – protected design
- Professional quality “Made in Germany”
- Hygrostat connection
- Durable, robust and reliably

Specification Overview

Operating range	0 to 100% r.H. / -15 °C to +35 °C
Dehumidification performance	ca. 0.35 kg/h
Air flow rate	40 - 120m ³ /h
Nominal air volume/ext. pressure	80m ³ /h / 50 Pa
Regeneration air/ext. pressure	15m ³ /h / 30 Pa
Dry air connection	ø 80 mm
Moist air connection	ø 38/50 mm
Electrical connection	230V - 50/60 Hz – ca. 0.45 kW
Dimensions	ca. 305 x 260 x 285 mm
Weight	ca. 9 kg

We are happy to provide further information



1890 247 266

DUBLIN +353 01 4048770
CORK +353 021 4930870
NI +44 078 92728580



info@crosshireservices.ie



www.crosshireservices.ie